



**NOTES:**

Item: AMOS10  
 Operating Speed: 0~300RPM, Higher speed can be custom  
 Working Temperature: -20°C ~ +80°C  
 Working Humidity: 10%~60%RH  
 Voltage Rating: 240VAC/DC  
 Current Rating: 2A  
 Dielectric Stength:500VAC@50Hz, 60s  
 Insulation Resistance:500MΩ@ 500VDC  
 Electrical Noise:1mΩMin  
 Contact Material :Precious metal  
 Lead wire: Teflon®UL 30AWG  
 Lead wire length:250mm  
 Material: Metal housing, plastic shaft  
 Drawings not actual size, dimensions are in millimeters

Model	NO. of Circuits	L
AMOS10-06	6	17.9
AMOS12-12	12	17.9

Drawn	JAM	<b>TOLERANGCE EXCEPT AS NOTED</b>  X.X ±.125 X.XX ±.015 X.XXX ±.005 ANGLES ± 0.5°		
Checked	TOM			
Checked	TOM			
CUSTOMER APPROVAL/DATE:			CUSTOMER:	
THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPEIETARY TO COSMAU TECHNOLOGY CO.,LIMITED NO REPRODUCTION OR PUBLICATION OF THIS DOCUMENT OR TI IS CONTENTS , IN WHOLE OR PART,SHALL BE MADE WIHOUT THE WILTTEN CONSENT FROM COSMAU.			P/N:	REV: <b>A.1</b>

THIRD ANGLE PROJECTION

