



NOTES:

Item: AMOS25
 Operating Speed: 0~300RPM, Higher speed can be custom
 Working Temperature: -20°C ~ +80°C
 Working Humidity: 10%~60%RH
 Voltage Rating: 240VAC/DC
 Current Rating: 2A
 Dielectric Stength:500VAC@50Hz, 60s
 Insulation Resistance:500MΩ@ 500VDC
 Electrical Noise:1mΩMin
 Contact Material :Precious metal
 Lead wire: Teflon®UL 28AWG
 Lead wire length:250mm
 Material: All Stainless Steel Structure
 Flange can be option
 Drawings not actual size, dimensions are in millimeters

Model	NO. of Circuits	L
AMOS25-12	12	27.2
AMOS25-24	24	42.8
AMOS25-36	36	59.4
AMOS25-48	48	74.0
AMOS25-60	60	91.9
AMOS25-72	72	107.5

Drawn	JAM	TOLERANGCE EXCEPT AS NOTED
Checked	TOM	
Checked	TOM	



CUSTOMER APPROVAL/DATE:

CUSTOMER:

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPEIETARY TO COSMAU TECHNOLOGY CO.,LIMITED NO REPRODUCTION OR PUBLICATION OF THIS DOCUMENT OR TI IS CONTENTS , IN WHOLE OR PART,SHALL BE MADE WIHOUT THE WILTTEN CONSENT FROM COSMAU.

P/N: REV:
A.1

THIRD ANGLE PROJECTION

