

**NOTES:**

Item: SMOS16  
 Operating Speed: 0~300RPM, Higher speed can be custom  
 Working Temperature: -20°C ~ +80°C  
 Working Humidity: 10%~60%RH  
 Voltage Rating: 240VAC/DC  
 Current Rating: 2A  
 Dielectric Stength:500VAC@50Hz, 60s  
 Insulation Resistance:500MΩ@ 500VDC  
 Electrical Noise:1mΩMin  
 Contact Material :Precious metal  
 Lead wire: Teflon®UL 30AWG  
 Lead wire length:250mm  
 Material: All Stainless Steel Structure  
 Flange can be option  
 Drawings not actual size, dimensions are in millimeters

Model	NO. of Circuits	L
SMOS16-12	12	21.7
SMOS16-24	24	32.5
SMOS16-36	36	43.3
SMOS16-48	48	54.1


Drawn	JAM	TOLERANGCE EXCEPT AS NOTED
Checked	TOM	
Checked	TOM	

**COSMAU** Global  
Rotating tomorrow

CUSTOMER APPROVAL/DATE:

CUSTOMER:

THIRD ANGLE PROJECTION



THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPEIETARY TO COSMAU TECHNOLOGY CO.,LIMITED NO REPRODUCTION OR PUBLICATION OF THIS DOCUMENT OR TI IS CONTENTS , IN WHOLE OR PART,SHALL BE MADE WIHOUT THE WILTTEN CONSENT FROM COSMAU.

P/N:                      REV:  
    **A.1**