



**NOTES:**

Item: SMOS20-F  
 Operating Speed: 0~300RPM, Higher speed can be custom  
 Working Temperature: -20°C ~ +80°C  
 Working Humidity: 10%~60%RH  
 Voltage Rating: 240VAC/DC  
 Current Rating: 2A  
 Dielectric Stength:500VAC@50Hz, 60s  
 Insulation Resistance:500MΩ@ 500VDC  
 Electrical Noise:1mΩMin  
 Contact Material :Precious metal  
 Lead wire: Teflon®UL 28AWG  
 Lead wire length:250mm  
 Material: All Stainless Steel Structure  
 Flange can be option  
 Drawings not actual size, dimensions are in millimeters

Model	NO. of Circuits	L
SMOS20-12-F	12	26.3
SMOS20-24-F	24	41.9
SMOS20-36-F	36	57.5

Drawn	JAM	TOLERANGCE EXCEPT AS NOTED
Checked	TOM	
Checked	TOM	



CUSTOMER APPROVAL/DATE:

CUSTOMER:

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPEIETARY TO COSMAU TECHNOLOGY CO.,LIMITED NO REPRODUCTION OR PUBLICATION OF THIS DOCUMENT OR TI IS CONTENTS , IN WHOLE OR PART,SHALL BE MADE WIHOUT THE WILTTEN CONSENT FROM COSMAU.

P/N:

REV:  
**A.1**

THIRD ANGLE PROJECTION

